

PRODUCTS CATALOGUE

"AT EASE IN YOUR CONSTRUCTION SITE"

www.ritmo.it





Ritmo meets all your welding needs in your jobsite



The information and photos in this publication are not binding and RITMO S.P.A. is free to make any alterations without prior notice.

A

DVANTAGE

RITMO



RITMO WORLDWIDE

Ritmo has professional distributors and resellers all over the world. Our staff is ready to assist you in English, Spanish, French, German, Arab, Italian, Russian and Portuguese.

TRAINING

From many years now, we have decided that the best way to grant a client/distributor a perfect knowledge of our products is to invest in custom training, in our own premises. These courses are aimed to teach how to operate the products in the best way, and how to supply the "first aid" when necessary.

PRESALES TECHNICAL ASSISTANCE

When a client or a potential client wants to buy us a product, it is our standard procedure to help find the best solution to its needs.

GLOBAL ADVICE

In such a technical field as ours, the customer requires the best assistance. Thanks to the experience developed along the years, and to the co-operation with several manufacturers, institutions, schools and training institutes, RITMO is able to give the most comprehensive advice to no matter which related issue. Our company is a long-time member of a UNIPLAST's (UNI-Italian National Plastics Standards Body) working group dedicated to the study and draw up of new standards within our field. The importance of this group is linked to the fact that the expansion of the plastic welding field ought to be followed by a crescent sensitivity for safety issues, so to have a sustainable and continuous growth. The working group prepares draws, hence present them to the UNI to be discussed and eventually transformed into new standards.

AFTER SALES TECHNICAL ASSISTANCE

Ritmo's Service Centre can solve all kind of technical issues, as well as overhaul our machines. Ritmo has other Service Centres abroad, linked to its official distributors.

STARTING AND TESTING

RITMO' technicians are prepared to make the starting and testing of workshop machines at the client' own premises, so that the fittings production can start almost immediately.



Ritmo
PLASTIC WELDING TECHNOLOGY



RITMO'S BUTT FUSION MACHINES: WORK PHILOSOPHY AVAILABLE TO EVERYONE!

- **MANUAL**

welding machines without hydraulic gearcase



- **HYDRAULIC**

welding machines with hydraulic gearcase



- **EASY LIFE SYSTEM** *HIGH LEVEL PERFORMANCE*

automated welding cycle

welding machines with special hydraulic gearcase

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF



- **ALL TERRAIN** *HIGH LEVEL PERFORMANCE*

self-contained generator on board

self-propelled

trolley with wheels

welding machines with special hydraulic gearcase

automated welding cycle

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF



- **CNC** *HIGH LEVEL PERFORMANCE*

automatic welding cycle

special hydraulic gearcase and machine body with

integrated mechanical extraction of heating plate

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF



ALL TERRAIN LINE - TRAILER LINE

HIGH LEVEL PERFORMANCE



DIFFERENCES BETWEEN ALL TERRAIN LINE AND TRAILER LINE


PLUS

**HIGH
PERFORMANCE**

**ENHANCES
PRODUCTIVITY**

	ALL TERRAIN LINE	TRAILER LINE
Working standards mm	√	√
Working standards "IPS /"DIPS	√	√
International standards ISO 21307 HIGH PRESSURE	√	√
Welds fittings	√	√
Easy Life Welding System	√	√
Data-logging	√	√
Wi-Fi Ready	√	√
PRE-SET 20 customized welding cycles	√	√
Intuitive control panel	√	√
GPS traceability	√	√
Report PDF	√	√
Self-contained Generator on-board	√	-
Heater/Facer on-board	√	√
Insert - Fast-locking system	√	√
Trolley with wheels	√	√
Self-propelled	√	-
Remotely wire-controlled up to 12 m (39 ft)	√	√
Carriage can be removed for in-ditch use	√	√
Lateral rollers	√	√





DELTA 500 ALL TERRAIN

DELTA 500 ALL TERRAIN is powered by a low-vibration diesel engine and equipped with front steering wheels and rear traction. The machine is suitable for welding pressure pipes (HDPE, PP) for the transportation of water, gas and other fluids up to Ø 500 mm (20 "IPS). Built according to the International standards ISO 21307 HIGH PRESSURE (machine works with a pressure range that is three times and a half higher than the ISO Low Pressure one. This enhances productivity, with a welding time saving up to 60%).

- Working range from Ø 200 to 500 mm (6" IPS ÷ 20" IPS).
- Welds fittings like elbows, tees, Y-branches and stub flanges.
- New RITMO Patented assisted system to open/close/lift clamps-heater-facer.
- Fast-locking system which allows to place and remove inserts in seconds.
- Intuitive control panel and large graphic display.
- Removable control panel with data-logging.
- Memory up to 4000 welding reports.
- GPS traceability.
- USB port for welding PDF report / data download / firmware upgrade
- Easy-life welding control system: hardware and software have been developed to interact to each other sharing data during the entire workflow. Once set the welding parameters up, the system guarantees the repetition of the welding cycles, avoiding errors. The operator only have to confirm the work phases on the just pushing a button. Possibility to pre-set 20 customized welding cycles.
- **Easy Life system is "Wi-Fi" ready and works together with the App "SET & GO - PRO".**
- Machine body and on-board generator easily removable for working in tight spaces.
- Machine can be powered using 230 V Three phase 50/60 Hz.
- Wheeled chassis designed to be lifted using a forklift.
- Two hydraulic rollers for pipe loading and unloading.
- On-board electric facer that is equipped with a safety microswitch.
- On-board generator removable for independent use.

STANDARD COMPOSITION



Machine body



Hydraulic
Rollers




Trolley



Control panel
with GPS



Milling cutter



Heating plate

TECHNICAL FEATURES

PLUS

200 ÷ 500 mm
 ISO 21307
 HIGH PRESSURE
 Enhances productivity
 Welding time saving
 Assisted system
 to open/close/lift
 clamps-heater-facer

Working range	200 ÷ 500 mm; 6" IPS ÷ 20" IPS
Materials	HDPE, PP For other materials contact RITMO S.P.A.
Power supply	self contained - diesel engine 230 V Three Phase 50/60 Hz
Total absorbed power	7250 W
Working temperature	180° ÷ 280° C (356° ÷ 536° F)
Outside temperature range	-10° ÷ 40° C (14° ÷ 104° F)
Dimensions machine body (W x D x H)	1822 x 1152 x 990 mm 71.7" x 45.4" x 39"
Dimensions trailer (W x D x H)	2955 x 1578 x 1370 mm 116.4" x 62.1" x 54"
Weight standard composition	1350 Kg 2976 lb)

ON REQUEST



Inserts
 Ø 200 ÷ 500 mm



Tool for flange
 necks



Track
 Conversion
 System



App
 "Set & Go Pro"

and:
 Inserts Ø 6" ÷ 18" IPS; 6" ÷ 18" DIPS; KIT for IN-DITCH USE,
 HS Roller 630; Plug for network power supply connection

Italy





EASY LIFE CONCEPT



EASY LIKE PUSHING A BUTTON

This is the concept that developed the EASY LIFE welding system: *“to simplify the work in the jobsite avoiding human mistakes”*; this is the philosophy that it holds in its name *“Style and Technology”* by RITMO. EASY LIFE is a whole RITMO’s project for all and accessible to everybody. Easy Life is **“Wi-Fi” ready and works together with the App “SET & GO - PRO”**.

HOW DOES IT WORK

Hardware and software have been developed to interact to each other sharing data during the entire workflow. Once set the welding parameters up, the system guarantees the repetition of the welding cycle, avoiding errors. The operator only has to confirm the work phases on the gear case when asked to, just pushing a button. Besides, during the “welding phase”, where sometimes some pressure adjustments are needed, the electronics system solve automatically this specific problem.

QUALITY IN WELDING

The Easy Life system incorporates a data-logging that saves the data in an internal hard-drive capable to store up to 4000 welds. Possibility to pre-set 50 customized welding cycles. The data will be available through PDF reports, downloadable in a USB pen drive.

EXTREME RELIABILITY

Born on 2002, the EASY LIFE system is now at its fourth evolution.

“SET & GO! PRO” APP

HIGH QUALITY ON BUTT FUSION WELDING



"SET & GO! PRO" a Professional application for smartphones and tablets (Android and iOS) that changes forever the way to work with the Ritmo Easy Life butt fusion machines.

"SET & GO! PRO" Put together the ease of use, innovation and quality, in a system with the advantages of a CNC welding system, but reducing significantly the costs of it.

ADVANTAGES

It eliminates the expensive hardware of a data-logging and offer the highest quality at the lowest cost.



PLUS

**EASY SETTING
WI-FI READY**

**GEOLOCATION
MAP**

**DATA-LOGGING
REPORT PDF**



watch the video



HOW DOES IT WORK?

Set-up the easy life welding machine through your smart-phone/tablet with few and easy steps: choose the international welding standards (ISO, DVS, UNI, ASTM, etc.), pipe diameter and SDR.

With the GPS and smartphone scanner you can collect, transfer, and store information by project name. You can record the exact location of each pipe weld as well as the construction site, you can scan pipe and fitting barcodes, scan operator badge, and take a photo before and after the installation.

With a detailed report at the end of each weld you have all the technical data with exact graphs and parameters to compare against international welding standards and geolocation map. You can quickly share the welding reports in pdf format via email and whatsapp or save them to your phone or on a cloud archive.

Choose "SET & GO! PRO" because safety and quality are part of your job!

WELDING REPORT
Welding = N° 46 - NO ERROR

Date (dd/mm/yy) = 16/02/18
Time (hh:mm) = 09:46

Standard
ISO 21307 (06/11) SINGLE LP

Diameter = 250 mm
SDR = 17
Thickness = 14.8mm
Material = PE

pt = 0.17MPa
T min = 200°C
T nom = 223°C
T max = 245°C
p1 = 20 bar
A = 20mm
p2 = 0 bar, t2 = 163 s
t3 = 5 s
t4 = 8 s
p3 = 20 bar, t5 = 1080 s

Model = BASIC 315 (V0,V1)
Piston area = 6.68 cm²
Serial = 99000006
Firmware version = 216
Next overhaul (mm/yy) = 10/18
Operator = Test operator
Job site = Ritmo
Remark = test welding

Diameter = 250 mm
SDR = 17
Thickness = 14.8mm
Material = PE
T heater = 223°C

Drag pressure pt = 3 bar
p1 + pt = 31 bar, t1 = 30 s
p2 = 0 bar, t2 = 163 s
t3 = 4 s
t4 = 8 s
p3 + pt = 31 bar, t5 = 1080 s
t total = 1269 s

OPERATOR'S BADGE
300000941424312017564039002030

JOINT TRACEABILITY 1
313701110081452040602025320078232530012

JOINT TRACEABILITY 2
313701110081452040602025320078232530012

GPS 45:23,39647 11:43,0569

PICTURES BEFORE

PICTURES AFTER

***** REPORT n.9 Easy Life v1.09 *****

Date: 02/02/16
Hour: 12:58
Set temperature HP: 200 C
Revision: 11/15
Serial number: 111200000
Diameter: 75 mm
Material: PP
SDR: 7.4
Operator: GIA
Job site: RIT

Remark:

*** WELDING DATA ***
Welding number: 9
Drag Pressure: 5 bar
P1: 40 bar
P2: 2 bar
P5: 40 bar
T1: 2s
T2: 30s
T3: 6s
T4: 4s
T5: 180s
Total joint time: 3'42"

Report by EASY LIFE

Report by
EASY LIFE + "SET & GO! PRO"



BUTT FUSION MACHINES REFERENCE



WORKING RANGE Ø mm	32	40	50	63	75	90	110	125	140	160	180	200	225	250	280	315	355	400	450	500	560	630	710	800	900	1000	1200	1400	1600	
GAMMA 160		40	50	63	75	90	110	125	140	160																				
DELTA 160 M	32	40	50	63	75	90	110	125	140	160																				
DELTA 200 M				63	75	90	110	125	140	160	180	200																		
BASIC 160		40	50	63	75	90	110	125	140	160																				
BASIC 200				63	75	90	110	125	140	160	180	200																		
BASIC 250					75	90	110	125	140	160	180	200	225	250																
BASIC 315						90	110	125	140	160	180	200	225	250	280	315														
BASIC 355								125	140	160	180	200	225	250	280	315	355													
COMPACT 355								125	140	160	180	200	225	250	280	315	355													
BASIC 160 EASY LIFE		40	50	63	75	90	110	125	140	160																				
BASIC 200 EASY LIFE				63	75	90	110	125	140	160	180	200																		
BASIC 250 EASY LIFE					75	90	110	125	140	160	180	200	225	250																
BASIC 315 EASY LIFE						90	110	125	140	160	180	200	225	250	280	315														
BASIC 355 EASY LIFE								125	140	160	180	200	225	250	280	315	355													
DELTA 500 EASY LIFE												200	225	250	280	315	355	400	450	500										
DELTA 630 EASY LIFE															280	315	355	400	450	500	560	630								
DELTA 500												200	225	250	280	315	355	400	450	500										
DELTA 630															280	315	355	400	450	500	560	630								
DELTA 800																				500	560	630	710	800						
DELTA 1000																						630	710	800	900	1000				
DELTA 1200																							710	800	900	1000	1200			
DELTA 1600																								800	900	1000	1200	1400	1600	
DELTA 250 TRAILER					75	90	110	125	140	160	180	200	225	250																
DELTA 355 TRAILER								125	140	160	180	200	225	250	280	315	355													
DELTA 355 ALL TERRAIN								125	140	160	180	200	225	250	280	315	355													
DELTA 500 TRAILER												200	225	250	280	315	355	400	450	500										
DELTA 500 ALL TERRAIN												200	225	250	280	315	355	400	450	500										
DELTA 630 TRAILER													225	250	280	315	355	400	450	500	560	630								
DELTA 630 ALL TERRAIN													225	250	280	315	355	400	450	500	560	630								
DELTA 1000 TRAILER																315	355	400	450	500	560	630	710	800	900	1000				
DELTA DRAGON 250 CNC					75	90	110	125	140	160	180	200	225	250																
DELTA DRAGON 315 CNC						90	110	125	140	160	180	200	225	250	280	315														
WORKING RANGE Ø mm	32	40	50	63	75	90	110	125	140	160	180	200	225	250	280	315	355	400	450	500	560	630	710	800	900	1000	1200	1400	1600	

CTS	IPS																																					
	1"	1¼"	1½"	2"	1"	1¼"	1½"	2"	3"	4"	5"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	42"	48"	52"	54"	63"						
GAMMA 160																																						
DELTA 160 M	•	•	•	•	•	•	•	•	•	•	•	•	•																									
DELTA 200 M																																						
BASIC 160					•	•	•	•	•	•	•	•	•																									
BASIC 200																																						
BASIC 250																																						
BASIC 315																																						
BASIC 355																																						
COMPACT 355																																						
BASIC 160 EASY LIFE					•	•	•	•	•	•	•	•	•																									
BASIC 200 EASY LIFE																																						
BASIC 250 EASY LIFE																																						
BASIC 315 EASY LIFE																																						
BASIC 355 EASY LIFE																																						
DELTA 500 EASY LIFE																																						
DELTA 630 EASY LIFE																																						
DELTA 500																																						
DELTA 630																																						
DELTA 800																																						
DELTA 1000																																						
DELTA 48"																																						
DELTA 1600																																						
DELTA TRAILER 250																																						
DELTA 355 TRAILER																																						
DELTA 355 ALL TERRAIN																																						
DELTA 500 TRAILER																																						
DELTA 500 ALL TERRAIN																																						
DELTA 630 TRAILER																																						
DELTA 630 ALL TERRAIN																																						
DELTA 1000 TRAILER																																						
IPS																																						
					1"	1¼"	1½"	2"	3"	4"	5"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	42"	48"	52"	54"	63"						

DIPS																																						
	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	24"	30"	36"	42"	48"	54"	60"																					
GAMMA 160																																						
DELTA 160 M	•	•																																				
DELTA 200 M	•	•	•																																			
BASIC 160	•	•																																				
BASIC 200	•	•	•																																			
BASIC 250	•	•	•	•																																		
BASIC 315	•	•	•	•	•																																	
BASIC 355	•	•	•	•	•	•																																
COMPACT 355	•	•	•	•	•	•	•																															
BASIC 160 EASY LIFE	•	•																																				
BASIC 200 EASY LIFE	•	•	•																																			
BASIC 250 EASY LIFE	•	•	•	•																																		
BASIC 315 EASY LIFE	•	•	•	•	•																																	
BASIC 355 EASY LIFE	•	•	•	•	•	•																																
DELTA 500 EASY LIFE																																						
DELTA 630 EASY LIFE																																						
DELTA 500																																						
DELTA 630																																						
DELTA 800																																						
DELTA 48"																																						
DELTA 1600																																						
DELTA TRAILER 250	•	•	•	•																																		
DELTA 355 TRAILER	•	•	•	•	•																																	
DELTA 355 ALL TERRAIN	•	•	•	•	•	•																																
DELTA 500 TRAILER	•	•	•	•	•	•	•																															
DELTA 500 ALL TERRAIN	•	•	•	•	•	•	•	•																														
DELTA 630 TRAILER	•	•	•	•	•	•	•	•	•																													
DELTA 630 ALL TERRAIN	•	•	•	•	•	•	•	•	•	•																												
DELTA 1000 TRAILER	•	•	•	•	•	•	•	•	•	•	•																											
DIPS																																						
	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	24"	30"	36"	42"	48"	54"	60"																					



RITMO S.p.A.
Via A. Volta, 35/37 - 35037
Bresseo di Teolo (PADOVA) ITALY

Ph. +39 049 9901888
Fax +39 049 9901993

info@ritmo.it
www.ritmo.it



Watch
the Corporate Video